

## Appliances properties: Heta A/S - Scan-Line 800

| Master data                  |                                |   |
|------------------------------|--------------------------------|---|
| Date of entry                | Mar 13, 2014                   |   |
| Manufacturer                 | Heta A/S                       |   |
| Model                        | Scan-Line 800                  |   |
| Nominal heat output [kW]     | 6                              |   |
| Continuous burning appliance | _                              |   |
| Type test standard           | DIN EN 13240                   |   |
| Year of testing              | 2011                           |   |
| Test laboratory              | Danish Technological Institute |   |
| Number of test laboratory    | 15                             |   |
| Number of test report        | 300-ELAB-1447-EN               |   |
| Flue gas values              |                                |   |
|                              | Woo                            | d |
| Flue gas mass flow [g/s]     | 5.                             | 3 |
| Flue gas mass flow [g/s]     | 27                             | 4 |
| Necessary flue draught [Pa]  | 1                              | 3 |

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)

Connectivity to the central heating system

General technical approval for room sealed operation

## Number of approval for room sealed operation

Z-43.12-325

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

<sup>\*</sup> A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Evaluation of emission data and efficiency Wood

| Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing | Evaluation             |
|---|------------------------|
| D - 1.BlmSchV   | Stufe 2                |
| A - Austrian regulation referred to Art 15a B-VG                            | ✓                      |
| CH - Swiss clean air act  | ✓                      |
| DK - Danish regulation for air pollution from wood burners                  | ✓                      |
| F - Crédit d'impôt à la transition énergétique                              | <b>√</b><br>7 <b>☆</b> |

## Evaluation of emission data and efficiency Lignite briquettes

| Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing | Evaluation |
|---|------------|
| D - 1.BlmSchV   | ļ.         |



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information