

Appliances properties: Brula GmbH - BRULA Feuerraum Typ C plus 90° L

Master data Date of entry Jan 19, 2023 Manufacturer Brula GmbH Model BRULA Feuerraum Typ C plus 90° L Continuous burning appliance Thermal output 146,000 Type test standard **DIN EN 15250** 2019 Year of testing **Test laboratory** DBI-Gastechnisches Institut gGmbH Freiberg Number of test laboratory 12 Number of test report F 19/11/0709 Flue gas values Wood Flue gas mass flow [g/s] 20.33 Flue gas mass flow [g/s] 187 Necessary flue draught [Pa] 13 Further important characteristics of the appliance Suitability for installation to a shared flue¹⁾ Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*}A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm : Masonry heater	Evaluation
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	✓
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	*

Evaluation of emission data and efficiency Lignite briquettes

Norm : Masonry heater	Evaluation
D - 1.BlmSchV	ļ.



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information