

Appliances properties: firetube GmbH - burner extension air 350 lang

Master data

Date of entry Jul 17, 2012

Manufacturer firetube GmbH

Model burner extension air 350 lang

Nominal heat output [kW] 14.9

Continuous burning appliance

Type test standard DIN EN 13240

Year of testing 2012

Test laboratory DBI-Gastechnisches Institut gGmbH Freiberg

Number of test laboratory 12



Flue gas values

	Wood	
Flue gas mass flow [g/s]	11	
Flue gas mass flow [g/s]	314	
Necessary flue draught [Pa]	12	

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

Evaluation of emission data and efficiency Wood

Norm DIN EN 13240 (Continuous burning): Roomheater with feeder firing	Evaluation
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	✓
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	✓ 7 ☆

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Continuous burning): Roomheater with feeder firing

D - 1.BlmSchV



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information