

Appliances properties: skantherm GmbH & Co. KG - samsø VI, VI Back (mehrfachbelegbar)

Alter of entry Alter of exterior Alter of exting Alter of exting Alter of exting Alter of ext laboratory Deutsche Kohle Marketing GmbH Alter of test laboratory Alter of test laboratory Alter of test report Alter of exterior Alter o			
Model samsø VI, VI Back (mehrfachbelegbar) Nominal heat output [kW] Continuous burning appliance Type test standard (Year of testing 1995 Test laboratory Deutsche Kohle Marketing GmbH Number of test laboratory 22 Number of test report 91 95 02 Filue gas values Type a mass flow [g/s] 8 Tilue gas mass flow [g/s] 19 Further important characteristics of the appliance Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system	Master data		
Model samsø VI, VI Back (mehrfachbelegbar) Nominal heat output [kW] Continuous burning appliance Pype test standard Pype test standard Pype test standard Polin 18891 Perst laboratory Deutsche Kohle Marketing GmbH Pumber of test laboratory Pumber of test report Price gas values Price gas mass flow [g/s] P	Date of entry	Mar 6, 2012	
Acontinuous burning appliance Type test standard (Your of testing Test laboratory Number of test laboratory Number of test report Flue gas values Flue gas mass flow [g/s] Number of test report Flue gas mass flow [g/s] Further important characteristics of the appliance Further important characteristics of the appliance Further important characteristics of the appliance	Manufacturer	skantherm GmbH & Co. KG	
Continuous burning appliance Type test standard DIN 18891 1995 Fest laboratory Deutsche Kohle Marketing GmbH Number of test laboratory 22 Number of test report 91 95 02 Flue gas values Flue gas mass flow [g/s] Recessary flue draught [Pa] Further important characteristics of the appliance Suitability for installation to a shared flue 1) Connectivity to the central heating system	Model	samsø VI, VI Back (mehrfachbelegbar)	
Type test standard (Year of testing 1995 Test laboratory Deutsche Kohle Marketing GmbH Number of test laboratory 22 Number of test report 91 95 02 Flue gas values Wood Flue gas mass flow [g/s] Rucessary flue draught [Pa] Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system	Nominal heat output [kW]	9	
Flue gas mass flow [g/s] 8 Flue gas mass flow [g/s] 92 Flue gas mass flow [g/s] 195 Flue gas mass flow	Continuous burning appliance	_	
The state of test laboratory Number of test laboratory Number of test report 22 Suitability for installation to a shared flue 1) Connectivity to the central heating system Deutsche Kohle Marketing GmbH 22 Wood Wood Flue gas values Wood Relue gas mass flow [g/s] 8 287 287 287 287 287 287 287	Type test standard	DIN 18891	
Number of test laboratory Number of test report 91 95 02 Flue gas values Flue gas mass flow [g/s] Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system	Year of testing	1995	
Flue gas values Flue gas walues Wood	Test laboratory	Deutsche Kohle Marketing GmbH	
Flue gas values Wood Flue gas mass flow [g/s] 8 Flue gas mass flow [g/s] 287 Necessary flue draught [Pa] 10 Further important characteristics of the appliance Suitability for installation to a shared flue 1) Connectivity to the central heating system	Number of test laboratory	22	
Wood Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance Suitability for installation to a shared flue 1) Connectivity to the central heating system	Number of test report	91 95 02	
Flue gas mass flow [g/s] Necessary flue draught [Pa] Further important characteristics of the appliance Suitability for installation to a shared flue 1) Connectivity to the central heating system	Flue gas values		Wood
Necessary flue draught [Pa] Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system	Flue gas mass flow [g/s]		8
Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system	Flue gas mass flow [g/s]		287
Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system	Necessary flue draught [Pa]		10
Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system			
Connectivity to the central heating system	Further important characteristics of the appliance		
	Suitability for installation to a shared flue ¹⁾		•
General technical approval for room sealed operation	Connectivity to the central heating system		_
	General technical approval for room sealed operation		_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm DIN EN 13240: Roomheater for wood logs	Evaluation
EU - Regulation (EU) 2015/1185 (Ecodesign)	
D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2024
A - Austrian regulation referred to Art 15a B-VG	
CH - Swiss clean air act	ļ
DK - Danish regulation for air pollution from wood burners	ļ
F - Crédit d'impôt à la transition énergétique	ļ
I - Italian Decree No. 186	ļ.

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BlmSchV	According to the transitional rule §26 the appliance can be used until 31.12.2024



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information