

Appliances properties: Bernhard Kaschütz GmbH - Firetherm 6 mit 1 Nachheizkasten

anufacturer bedel Fire cominal heat output [kW] coclared nominal space heating output [kW] firtial load [kW] 3.3 continuous burning appliance ermal output pe test standard car of testing st laboratory were sumber of test laboratory Ber 6.6 6.7 6.8 7 8.8 8.8 8.9 8.9 8.9 8.9 8.9		
ordel Fire ominal heat output [kW] 6.6 ordared nominal space heating output [kW] 6 ortial load [kW] 3.3 ontinuous burning appliance overmal output	therm 6 mit 1 Nachheizkasten EN 13229	
ominal heat output [kW] 6.6 cclared nominal space heating output [kW] 6 critial load [kW] 3.3 continuous burning appliance cermal output pe test standard DIN car of testing 201 st laboratory Ver umber of test laboratory 8	EN 13229	
cclared nominal space heating output [kW] 6 artial load [kW] 3.3 antinuous burning appliance eermal output pe test standard DIN aar of testing 201 st laboratory Verumber of test laboratory 8	5	
artial load [kW] 3.3 continuous burning appliance dermal output	5	
portinuous burning appliance dermal output pe test standard par of testing st laboratory Uer Jumber of test laboratory 8	5	
pe test standard DIN par of testing 201 st laboratory Ver umber of test laboratory 8	5	
pe test standard DIN ear of testing 201 st laboratory Ver umber of test laboratory 8	5	
st laboratory Verumber of test laboratory 8	5	
st laboratory Ver umber of test laboratory 8		
umber of test laboratory 8	over a very Conservation of the latest the l	
•	Versuchs- und Forschungsanstalt der Hafner Österreichs pratory 8	
umber of test report VH		
	F-15-006-P	
lue gas values		
	Wood	
ue gas mass flow [g/s]	43.5	
ue gas mass flow [g/s]	169.5	
ecessary flue draught [Pa]	12.5	

Further important characteristics of the appliance

Suitability for installation to a shared flue¹⁾

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	*
DK - Danish regulation for air pollution from wood burners	*
F - Crédit d'impôt à la transition énergétique	√ 7★

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	ļ.



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information