

Appliances properties: Rizzoli GmbH - RVE40

Master data	
Date of entry	May 11, 2017
Manufacturer	Rizzoli GmbH
Model	RVE40
Nominal heat output [kW]	7.4
Continuous burning appliance	_
Type test standard	DIN EN 12815
Year of testing	2014
Test laboratory	ACTECO SRL
Number of test laboratory	33
Number of test report	1880-CPR-031-14
Flue gas values	Wood
	Wood 8.6
Flue gas mass flow [g/s]	
Flue gas mass flow [g/s] Flue gas mass flow [g/s]	8.6
Flue gas mass flow [g/s] Flue gas mass flow [g/s] Necessary flue draught [Pa]	8.6 200

Suitability for installation to a shared flue 1)

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm : Cookers Evaluation Evaluation

D - 1.BlmSchV	Stufe 2 Grandfathering
- Austrian regulation referred to Art. 15a B-VG	2015
H - Swiss clean air act	✓
- Crédit d'impôt à la transition énergétique	✓.

Evaluation of emission data and efficiency Lignite briquettes

Norm : Cookers	Evaluation
D - 1.BImSchV	!

Evaluation of emission data and efficiency Pellets

Norm : Cookers	Evaluation
D - 1.BlmSchV	!



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information