

Appliances properties: Rüegg Cheminée Schweiz AG - Uranus 510 HK flach Tunnel Stil mit Nachschaltheizfläche

Master data

Date of entry Sep 25, 2012

Manufacturer Rüegg Cheminée Schweiz AG

Model Uranus 510 HK flach Tunnel Stil mit Nachschaltheizfläche

Nominal heat output [kW] 11

Declared nominal space heating output [kW] 11

Type test standard DIN EN 13229

Year of testing 2012

Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH

Number of test laboratory 2

Number of test report RRF - 29 07 1513/RRF - 02 389

Flue gas values

Continuous burning appliance

	Wood	
Flue gas mass flow [g/s]	10.6	
Flue gas mass flow [g/s]	175	
Necessary flue draught [Pa]	14	

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*}A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

orm : Inset appliances (with closed firedoor)	Evaluation
BlmSchV	Stufe 2
strian regulation referred to Art 15a B-VG	✓
Swiss clean air act	✓
- Crédit d'impôt à la transition énergétique	•

Evaluation of emission data and efficiency Lignite briquettes	
Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	1



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information