

## Appliances properties: Rüegg Cheminée Schweiz AG - Axinit Front S

Master data

Date of entry Oct 21, 2013

**Manufacturer** Rüegg Cheminée Schweiz AG

Model Axinit Front S

Nominal heat output [kW] 14.2

Declared nominal space heating output [kW] 14

Continuous burning appliance

Type test standard DIN EN 13229

Year of testing 2013

Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH

Number of test laboratory

Number of test report RRF - 29 13 3411



Flue gas values

	Wood	
Flue gas mass flow [g/s]	10.6	
Flue gas mass flow [g/s]	284	
Necessary flue draught [Pa]	12	

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system



<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

\* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

orm : Inset appliances (with closed firedoor)	Evaluation
BlmSchV	Stufe 2
strian regulation referred to Art 15a B-VG	✓
Swiss clean air act	✓
- Crédit d'impôt à la transition énergétique	•

Evaluation of emission data and efficiency Lignite briquettes	
Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	1



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information