

Master data

Appliances properties: Wodtke GmbH - soleo.nrg H10 6kW (PO03-11) RLU

Date of entry

Nov 7, 2018

Manufacturer

Wodtke GmbH

Model soleo.nrg H10 6kW (PO03-11) RLU

Nominal heat output [kW]

Continuous burning appliance

Type test standard DIN EN 14785

Year of testing 2018

Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH

Number of test laboratory 2

Number of test report RRF - 85 17 4767-1

Flue gas values

	Pellets
Flue gas mass flow [g/s]	4.7
Flue gas mass flow [g/s]	189
Necessary flue draught [Pa]	9

Further important characteristics of the appliance

Suitability for installation to a shared flue¹⁾

Connectivity to the central heating system

General technical approval for room sealed operation


Number of approval for room sealed operation

Z-43.12-240

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*}A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information