

Appliances properties: Dovre N.V. - 2180CB

Master data

Date of entry

Manufacturer

Dovre N.V.

Model

2180CB

Nominal heat output [kW]

Declared nominal space heating output [kW]

Continuous burning appliance

Type test standard

Apr 16, 2015

Dovre N.V.

15

15

DIN EN 13229

Year of testing 2013
Test laboratory LABORATORY K.V.B.G. - A.R.G.B.

Number of test laboratory 17
Number of test report H0063



Flue gas values

	Wood	
Flue gas mass flow [g/s]	13.6	
Flue gas mass flow [g/s]	326	
Necessary flue draught [Pa]	12	

Further important characteristics of the appliance

Suitability for installation to a shared flue¹⁾

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

orm : Inset appliances (with closed firedoor)	Evaluation
1.BImSchV	Stufe 2
ustrian regulation referred to Art 15a B-VG	_
Swiss clean air act	✓
Crédit d'impôt à la transition énergétique	✓

Evaluation of emission data and efficiency Lignite briquettes	
Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	I



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information