

Appliances properties: Spartherm Feuerungstechnik GmbH - Prismo 550/450

ubmitted to the HKI Industrieverband e.V.	Nov 26, 2011 Spartherm Feuerungstechnik GmbH Prismo 550/450 5 DIN 18895 1996
el inal heat output [kW] inuous burning appliance test standard of testing her important characteristics of the appliance bility for installation to a shared flue ¹⁾ hectivity to the central heating system val technical approval for room sealed operation unsealed operation it is possible to install the appliances to a shared flue system (ple half of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance to ubmitted to the HKI Industrieverband e.V.	Prismo 550/450 5 DIN 18895 1996
inal heat output [kW] inuous burning appliance test standard of testing her important characteristics of the appliance bility for installation to a shared flue ¹⁾ nectivity to the central heating system eral technical approval for room sealed operation unsealed operation it is possible to install the appliances to a shared flue system (ple half of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance to ubmitted to the HKI Industrieverband e.V.	5 DIN 18895 1996
inuous burning appliance test standard of testing her important characteristics of the appliance bility for installation to a shared flue ¹⁾ nectivity to the central heating system wal technical approval for room sealed operation unsealed operation it is possible to install the appliances to a shared flue system (ple half of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance to ubmitted to the HKI Industrieverband e.V.	DIN 18895 1996
test standard of testing her important characteristics of the appliance bility for installation to a shared flue ¹⁾ nectivity to the central heating system oral technical approval for room sealed operation unsealed operation it is possible to install the appliances to a shared flue system (ple half of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance to ubmitted to the HKI Industrieverband e.V. hereby confirms compliance to ubmitted to the HKI Industrieverband e.V.	DIN 18895 1996
of testing her important characteristics of the appliance bility for installation to a shared flue ¹⁾ hectivity to the central heating system ral technical approval for room sealed operation unsealed operation it is possible to install the appliances to a shared flue system (ple half of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance to ubmitted to the HKI Industrieverband e.V. en check mark with a "1" indicates that the requirements of the 1st BImSchV are fulf	1996
her important characteristics of the appliance bility for installation to a shared flue ¹⁾ nectivity to the central heating system aral technical approval for room sealed operation unsealed operation it is possible to install the appliances to a shared flue system (ple half of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance to ubmitted to the HKI Industrieverband e.V. en check mark with a "1" indicates that the requirements of the 1st BImSchV are fulf	
bility for installation to a shared flue ¹⁾ nectivity to the central heating system aral technical approval for room sealed operation unsealed operation it is possible to install the appliances to a shared flue system (ple nalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance to ubmitted to the HKI Industrieverband e.V. en check mark with a "1" indicates that the requirements of the 1st BImSchV are fulf	
bility for installation to a shared flue ¹⁾ nectivity to the central heating system aral technical approval for room sealed operation unsealed operation it is possible to install the appliances to a shared flue system (ple nalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance to ubmitted to the HKI Industrieverband e.V. en check mark with a "1" indicates that the requirements of the 1st BImSchV are fulf	
ectivity to the central heating system ral technical approval for room sealed operation unsealed operation it is possible to install the appliances to a shared flue system (ple half of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance of ubmitted to the HKI Industrieverband e.V. en check mark with a "1" indicates that the requirements of the 1st BImSchV are fulf	
eral technical approval for room sealed operation unsealed operation it is possible to install the appliances to a shared flue system (ple half of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance ubmitted to the HKI Industrieverband e.V. en check mark with a "1" indicates that the requirements of the 1st BImSchV are fulf	_
unsealed operation it is possible to install the appliances to a shared flue system (ple nalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance v ubmitted to the HKI Industrieverband e.V. en check mark with a "1" indicates that the requirements of the 1st BImSchV are fulf	_
nalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance of ubmitted to the HKI Industrieverband e.V. en check mark with a "1" indicates that the requirements of the 1st BImSchV are fulf	
ubmitted to the HKI Industrieverband e.V. en check mark with a "1" indicates that the requirements of the 1st BImSchV are fulf	ease see installation manual).
en check mark with a "1" indicates that the requirements of the 1st BImSchV are fulf hows that the transitional regulation of the 1st BImSchV is fulfilled and a red line me	with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has
nows that the transitional regulation of the 1st bimScriv is fulfilled and a red line me	illed, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow che
uation of emission data and efficiency Wood	
n : Inset appliances (with closed firedoor)	Evaluation
BImSchV Acco	ording to the transitional rule §26 the appliance can be used until 31.12.2024

ļ

ļ

I

A - Austrian regulation referred to Art 15a B-VG

CH - Swiss clean air act

F - Crédit d'impôt à la transition énergétique

Evaluation of emission data and efficiency Lignite briquettes		
Norm : Inset appliances (with closed firedoor)	Evaluation	
D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2024	

Emission evaluation legend

Stufe 2	Compliant with the requirements of the 2nd stage of the 1.BImSchV (only for Germany)
Stufe 1	Compliant with the requirements of the 1st stage of the 1.BImSchV (only for Germany)
2015	Compliant with the requirements of the Austrian Agreement pursuant to Art. 15a B-VG from 2015 (applies only to Austria)
7☆	Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 7* of the Flamme Verte Label
6☆	Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 6* of the Flamme Verte Label
5☆	Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 5* of the Flamme Verte Label
*	Compliant with the requirements of the 1 star stage in Italy.
**	Compliant with the requirements of the 2 star stage in Italy.
***	Compliant with the requirements of the 3 star stage in Italy.
***	Compliant with the requirements of the 4 star stage in Italy.
	Compliant with the requirements of the 5 star stage in Italy.
	Fulfils the requirements
\checkmark	Complies with requirements of the transition ruling (1.BImSchV)
-	Requirements are not fulfilled
—	No information/unknown
	No measuring values are available for this fuel, operation with this fuel is not permitted
Nosv	mbol means that there are no requirements

No symbol means that there are no requirements. Here you will find further information