

Appliances properties: Camina & Schmid Feuerdesign und Technik GmbH & Co. KG - Profi Plus, Profi K, Profi K Kristall, Profi R, Profi Concept

Master data

Date of entry Feb 21, 2008

 Manufacturer
 Camina & Schmid Feuerdesign und Technik GmbH & Co. KG

 Model
 Profi Plus, Profi K, Profi K Kristall, Profi R, Profi Concept

Nominal heat output [kW] 12

Continuous burning appliance

Type test standard DIN EN 13229

Year of testing 2007

Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH

Number of test laboratory 2

Number of test report RRF-29 07 1054

Flue gas values

	Wood
Flue gas mass flow [g/s]	11.3
Flue gas mass flow [g/s]	270
Necessary flue draught [Pa]	12

Further important characteristics of the appliance

Suitability for installation to a shared flue¹⁾



Connectivity to the central heating system



On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

General technical approval for room sealed operation

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*}A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

CH - Swiss clean air act

Norm : Inset appliance with flat-layer firing	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	✓

Norm: Inset appliance with flat-layer firing Evaluation D - 1.BlmSchV According to the transitional rule §26 the appliance can be used until 31.12.2024



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information