

Appliances properties: Oranier Heiztechnik GmbH - KE 900 - 7930 11

Master data		
Date of entry	Oct 19, 2010	
Manufacturer	Oranier Heiztechnik GmbH	
Model	KE 900	
Product code	7930 11	
Nominal heat output [kW]	9	
Continuous burning appliance	_	
ype test standard	DIN 18895	
fear of testing	1994	
Number of test report	95 94 16	
Flue gas values		
		Wood
Flue gas mass flow [g/s]		9
lue gas mass flow [g/s]		390
Necessary flue draught [Pa]		12
Further important characteristics of the appliance		
Suitability for installation to a shared flue ¹⁾		_
Connectivity to the central heating system		_
General technical approval for room sealed operation		_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2020

Evaluation of emission data and efficiency Lignite briquettes

Evaluation of emission data and efficiency Wood

F - Crédit d'impôt à la transition énergétique

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing

D - 1.BImSchV

According to the transitional rule §26 the appliance can be used until 31.12.2020



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information