

## Appliances properties: HWAM A/S - WIKING Mala 8

Date of entry Sep 25, 2020 Manufacturer HWAM A/S Model WikiNG Mala 8 Nominal heat output [kW] 4.5  Continuous burning appliance Type test standard DIN EN 13240 Year of testing 2020 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 Number of test report RRF - 40 20 5496-2  Flue gas mass flow [g/s] Flue gas mass flow [g/s] 1.02  Flue gas mass flow [g/s] 1.2  Further important characteristics of the appliance  Sultability for installation to a shared flue <sup>1)</sup> Connectivity to the central heating system			
Manufacturer  Model  WiKING Mala 8  Nominal heat output [kW]  4.5  Continuous burning appliance  Type test standard  DIN EN 13240  Year of testing  2020  Test laboratory  RRF Rhein-Ruhr-Feuerstattenprüfstelle GmbH  Number of test laboratory  2 RRF - 40 20 5496-2  Flue gas values  Flue gas sass flow [g/s]  Necessary flue draught [Pa]  Further important characteristics of the appliance  Suitability for installation to a shared flue 11	Master data		
Manufacturer Model WiKING Mala 8 Nominal heat output [kW] 4.5  Continuous burning appliance Type test standard DIN EN 13240 Year of testing 2020 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 RRF- 40 20 5496-2  Flue gas values  Flue gas mass flow [g/s] Necessary flue draught [Pa]  Further important characteristics of the appliance  HWAM A/S WIKING Mala 8 WIKING Mala 9 WIKING Mala 8 WIKING Mala 9 WIKING Mala 19	Date of entry	Sep 25, 2020	
Nominal heat output [kW]  Continuous burning appliance  Type test standard  DIN EN 13240  Year of testing  2020  RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH  Number of test laboratory  Number of test report  RRF - 40 20 5496-2  Flue gas values  Wood  Flue gas mass flow [g/s]  Flue gas mass flow [g/s]  Necessary flue draught [Pa]  Further important characteristics of the appliance  Suitability for installation to a shared flue 1)			
Continuous burning appliance  Type test standard  DIN EN 13240  Year of testing  2020  RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH  Number of test laboratory  RRF - 40 20 5496-2  Flue gas values  Wood  Flue gas mass flow [g/s]  Flue gas mass flow [g/s]  Necessary flue draught [Pa]  Further important characteristics of the appliance  Suitability for installation to a shared flue 1)	Model	WIKING Mala 8	
Type test standard  Year of testing  2020  Test laboratory  RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH  Number of test laboratory  2  Number of test report  RRF - 40 20 5496-2  Flue gas walues  Wood  Flue gas mass flow [g/s]  Flue gas mass flow [g/s]  Necessary flue draught [Pa]  Further important characteristics of the appliance  Suitability for installation to a shared flue <sup>1)</sup>	Nominal heat output [kW]	4.5	
Year of testing Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory RRF - 40 20 5496-2  Flue gas values  Wood Flue gas mass flow [g/s] 4.02 Flue gas mass flow [g/s] 251 Necessary flue draught [Pa] 12  Further important characteristics of the appliance	Continuous burning appliance	_	
Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 Number of test report RRF - 40 20 5496-2  Flue gas values  Wood Flue gas mass flow [g/s] 4.02 Flue gas mass flow [g/s] 251 Necessary flue draught [Pa] 12  Further important characteristics of the appliance  Suitability for installation to a shared flue 1)	Type test standard	DIN EN 13240	
Number of test laboratory Number of test report  RRF - 40 20 5496-2  Flue gas values  Wood  Flue gas mass flow [g/s] 4.02  Flue gas mass flow [g/s] 251  Necessary flue draught [Pa] 12  Further important characteristics of the appliance  Suitability for installation to a shared flue 1)	Year of testing	2020	
Flue gas values    Flue gas walues   Wood	Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
Flue gas values  Wood  Flue gas mass flow [g/s] 4.02  Flue gas mass flow [g/s] 251  Necessary flue draught [Pa] 12  Further important characteristics of the appliance  Suitability for installation to a shared flue <sup>1)</sup>	Number of test laboratory	2	
Flue gas mass flow [g/s] 4.02 Flue gas mass flow [g/s] 251 Necessary flue draught [Pa] 12  Further important characteristics of the appliance	Number of test report	RRF - 40 20 5496-2	
Flue gas mass flow [g/s]  Flue gas mass flow [g/s]  Necessary flue draught [Pa]  Further important characteristics of the appliance  Suitability for installation to a shared flue 1)	Flue gas values		
Flue gas mass flow [g/s]  Necessary flue draught [Pa]  Further important characteristics of the appliance  Suitability for installation to a shared flue <sup>1)</sup>			Wood
Necessary flue draught [Pa]  Further important characteristics of the appliance  Suitability for installation to a shared flue <sup>1)</sup>	Flue gas mass flow [g/s]		4.02
Further important characteristics of the appliance  Suitability for installation to a shared flue <sup>1)</sup>	Flue gas mass flow [g/s]		251
Suitability for installation to a shared flue <sup>1)</sup>	Necessary flue draught [Pa]		12
Suitability for installation to a shared flue <sup>1)</sup>			
	Further important characteristics of the appliance		
Connectivity to the central heating system	Suitability for installation to a shared flue <sup>1)</sup>		_
	Connectivity to the central heating system		-

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>\*</sup> A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Evaluation of emission data and efficiency Wood

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	<b>✓</b>
DK - Danish regulation for air pollution from wood burners	✓
F - Crédit d'impôt à la transition énergétique	7☆

## Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BlmSchV	



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information