

Appliances properties: Nordpeis AS - Uno5

Nominal heat output [kW] 4 Continuous burning appliance	Master data		
Manufacturer Nordpeis AS Model Uno5 Nominal heat output [kW] 4 Continuous burning appliance Type test standard Year of testing 2016 RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory RRF - 40 16 4289 Flue gas walues Wood Flue gas mass flow [g/s] 3.4 Flue gas mass flow [g/s] 320	Data of autor	hd 40, 2046	
Model Uno5 Nominal heat output [kW] 4 Continuous burning appliance			
Nominal heat output [kW] 4 Continuous burning appliance	Manufacturer	Nordpeis AS	
Type test standard DIN EN 13240 Year of testing 2016 Rest laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 Number of test report RRF - 40 16 4289 Flue gas walues Wood Flue gas mass flow [g/s] 3.4 Flue gas mass flow [g/s] 320	Model	Uno5	
Type test standard Year of testing 2016 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory RRF - 40 16 4289 Flue gas values Wood Flue gas mass flow [g/s] SIN EN 13240 2016 RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH RRF - 40 16 4289 Wood 3.4 Flue gas mass flow [g/s] 3.20	Nominal heat output [kW]	4	
Year of testing Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 Number of test report RRF - 40 16 4289 Flue gas values Wood Flue gas mass flow [g/s] 3.4 Flue gas mass flow [g/s] 320	Continuous burning appliance	_	
RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory Number of test report RRF - 40 16 4289 Flue gas values Wood Flue gas mass flow [g/s] 3.4 Flue gas mass flow [g/s] 320	Type test standard	DIN EN 13240	
Number of test laboratory Number of test report RRF - 40 16 4289 Flue gas values Wood Flue gas mass flow [g/s] 3.4 Flue gas mass flow [g/s] 320	Year of testing	2016	
Number of test report RRF - 40 16 4289	Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
Flue gas values Wood Flue gas mass flow [g/s] 3.4 Flue gas mass flow [g/s] 320	Number of test laboratory	2	
Wood Flue gas mass flow [g/s] 3.4 Flue gas mass flow [g/s] 320	Number of test report	RRF - 40 16 4289	
Wood Flue gas mass flow [g/s] 3.4 Flue gas mass flow [g/s] 320			
Flue gas mass flow [g/s] 3.4 Flue gas mass flow [g/s] 320	Flue gas values		
Flue gas mass flow [g/s] 320			Wood
	Flue gas mass flow [g/s]		3.4
Necessary flue draught [Pa] 12	Flue gas mass flow [g/s]		320
	Necessary flue draught [Pa]		12

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	✓
DK - Danish regulation for air pollution from wood burners	✓
F - Crédit d'impôt à la transition énergétique	7☆

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BlmSchV	



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information