

## Appliances properties: Wodtke GmbH - Kompakt KE 01.6

Master data

Date of entryJan 14, 2009ManufacturerWodtke GmbH

Model Kompakt KE 01.6

Nominal heat output [kW]

Continuous burning appliance

Type test standard DIN 18892

Year of testing 1986

Test laboratory Wodtke GmbH DIN Certco Werksprüfstelle

Number of test laboratory 16
Number of test report 85/19



Flue gas values

	Wood
Flue gas mass flow [g/s]	6
Flue gas mass flow [g/s]	350
Necessary flue draught [Pa]	16

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system

## General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

<sup>\*</sup>A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Norm : Inset appliances with feeder firing D - 1.BImSchV F - Crédit d'impôt à la transition énergétique

## Evaluation of emission data and efficiency Lignite briquettes

Evaluation of emission data and efficiency Wood

Norm : Inset appliances with feeder firing

D - 1.BImSchV

Evaluation



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information