

Appliances properties: Dovre N.V. - Vista 900

Master data		
Date of entry	May 11, 2017	
ManufacturerDovre N.V.ModelVista 900Nominal heat output [kW]14.1		
Declared nominal space heating output [kW]	14	
Continuous burning appliance	_	
Type test standard	DIN EN 13229	
Year of testing	2015	
Test laboratory	LABORATORY K.V.B.G A.R.G.B.	
Number of test laboratory	17	
Number of test report	H/2015/0077	
Flue gas values		
		Wood
Flue gas mass flow [g/s]		274
Necessary flue draught [Pa]		12
Further important characteristics of the appliance		
Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾		_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	✓
CH - Swiss clean air act	✓
DK - Danish regulation for air pollution from wood burners	✓
F - Crédit d'impôt à la transition énergétique	7☆

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	Ţ.



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information