

Appliances properties: Hase Kaminofenbau GmbH - Obelisk

Master data		
Date of entry	Nov 15, 2011	
Manufacturer	Hase Kaminofenbau GmbH	
Model	Obelisk	
Nominal heat output [kW]	10	
Continuous burning appliance	_	
Type test standard	DIN 18891	
Year of testing	1992	
Test laboratory	RWE Rheinbraun AG	
Number of test laboratory	4.1	
Number of test report	RBW-VF1-Hn 50/92	
Flue aga values		
Flue gas values		
		Wood
Flue gas mass flow [g/s]		14
Flue gas mass flow [g/s]		265
Necessary flue draught [Pa]		11
Further important characteristics of the appliance		
Suitability for installation to a shared flue ¹⁾		_
Connectivity to the central heating system		_
General technical approval for room sealed operation		_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing D - 1.BImSchV F - Crédit d'impôt à la transition énergétique Evaluation Evaluation F - Crédit d'impôt à la transition énergétique

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing

Evaluation

D - 1.BImSchV





No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information