



Appliances properties: TIBA AG - T-LINE eco2 Hochversion ab S/N 1600

Master data

Date of entry Mar 9, 2017

Manufacturer TIBA AG

Model T-LINE eco2 Hochversion ab S/N 1600

Continuous burning appliance

Thermal output 79074 kJ

Type test standard DIN EN 15250

Year of testing 2014

Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH

Number of test laboratory 2

Number of test report RRF - 50 14 3776



Flue gas values

	Wood	
Flue gas mass flow [g/s]	8.7	
Flue gas mass flow [g/s]	192	
Necessary flue draught [Pa]	13	

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system



General technical approval for room sealed operation



Number of approval for room sealed operation

Z-43.12-258

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).



This appliance is authorized to use the HKI quality label.

Evaluation of emission data and efficiency Wood	
Norm : Slow heat release appliances	Evaluation
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	2015
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	✓ 7♠



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information