



## Appliances properties: Spartherm Feuerungstechnik GmbH - Varia 1Vh / 2Lh / 3Rh / 3RLh / FDh (Bauart A; ab 1996)

### Master data

<b>Date of entry</b>	Mar 6, 2012
<b>Manufacturer</b>	Spartherm Feuerungstechnik GmbH
<b>Model</b>	Varia 1Vh / 2Lh / 3Rh / 3RLh / FDh (Bauart A; ab 1996)
<b>Nominal heat output [kW]</b>	11
<b>Continuous burning appliance</b>	—
<b>Type test standard</b>	DIN 18895
<b>Year of testing</b>	1996
<b>Test laboratory</b>	Deutsche Kohle Marketing GmbH
<b>Number of test laboratory</b>	22
<b>Number of test report</b>	RO - 95 96 30

### Flue gas values

	Wood
<b>Flue gas mass flow [g/s]</b>	10.9
<b>Flue gas mass flow [g/s]</b>	390
<b>Necessary flue draught [Pa]</b>	12

### Further important characteristics of the appliance

<b>Suitability for installation to a shared flue<sup>1)</sup></b>	—
<b>Connectivity to the central heating system</b>	—
<b>General technical approval for room sealed operation</b>	—

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

\* A green check mark with a „1“ indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a „2“ indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Evaluation of emission data and efficiency Wood

### Norm : Inset appliances (with closed firedoor)

### Evaluation

D - 1.BImSchV

!

According to the transitional rule §26 the appliance can be used until 31.12.2024

A - Austrian regulation referred to Art 15a B-VG

!

CH - Swiss clean air act

!

F - Crédit d'impôt à la transition énergétique

!

## Evaluation of emission data and efficiency Lignite briquettes

### Norm : Inset appliances (with closed firedoor)

### Evaluation

D - 1.BImSchV

!

According to the transitional rule §26 the appliance can be used until 31.12.2024

## Emission evaluation legend

---

-  Stufe 2 Compliant with the requirements of the 2nd stage of the 1.BImSchV (only for Germany)
-  Stufe 1 Compliant with the requirements of the 1st stage of the 1.BImSchV (only for Germany)
-  2015 Compliant with the requirements of the Austrian Agreement pursuant to Art. 15a B-VG from 2015 (applies only to Austria)
-  7★ Compliant with the requirements for the „Crédit d'impôt“ promotion in France, the fireplace complies with the classification 7\* of the Flamme Verte Label
-  6★ Compliant with the requirements for the „Crédit d'impôt“ promotion in France, the fireplace complies with the classification 6\* of the Flamme Verte Label
-  5★ Compliant with the requirements for the „Crédit d'impôt“ promotion in France, the fireplace complies with the classification 5\* of the Flamme Verte Label
-  ★ Compliant with the requirements of the 1 star stage in Italy.
-  ★★ Compliant with the requirements of the 2 star stage in Italy.
-  ★★★ Compliant with the requirements of the 3 star stage in Italy.
-  ★★★★ Compliant with the requirements of the 4 star stage in Italy.
-  ★★★★★ Compliant with the requirements of the 5 star stage in Italy.
-  Fulfils the requirements
-  Complies with requirements of the transition ruling (1.BImSchV)
-  Requirements are not fulfilled
-  No information/unknown
-  No measuring values are available for this fuel, operation with this fuel is not permitted

No symbol means that there are no requirements.

Here you will find further information