

Appliances properties: Wamsler Haus- und Küchentechnik GmbH - ILSEBORG KAMINOFEN TÜR V'GOLD.9kW - 1979088

Manufacturer Model ILSEBORG KAMINOFEN TÜR V'GOLD.9kW Product code 1979088 Jominal heat output [kW] Continuous burning appliance Type test standard Product cot testing DIN 18891 Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system	Master data	
Manufacturer Model ILSEBORG KAMINOFEN TÜR V'GOLD.9kW Product code 1979088 Sominal heat output [kW] Continuous burning appliance Type test standard Product code DIN 18891 DIN 18891 Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system Seneral technical approval for room sealed operation	Date of entry	May 21, 2011
Product code 1979088 Joninal heat output [kW] 9 Continuous burning appliance Type test standard DIN 18891 Fear of testing 1999 Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system General technical approval for room sealed operation	Manufacturer	Wamsler Haus- und Küchentechnik GmbH
Alominal heat output [kW] Continuous burning appliance Type test standard DIN 18891 1999 Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system General technical approval for room sealed operation	Model	ILSEBORG KAMINOFEN TÜR V'GOLD.9kW
Continuous burning appliance Type test standard DIN 18891 fear of testing Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system General technical approval for room sealed operation	Product code	1979088
Type test standard Tear of testing DIN 18891 1999 Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system General technical approval for room sealed operation	Nominal heat output [kW]	9
Further important characteristics of the appliance Suitability for installation to a shared flue 1) Connectivity to the central heating system General technical approval for room sealed operation	Continuous burning appliance	_
Further important characteristics of the appliance Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system General technical approval for room sealed operation	Type test standard	DIN 18891
Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system General technical approval for room sealed operation	Year of testing	1999
Suitability for installation to a shared flue ¹⁾ Connectivity to the central heating system General technical approval for room sealed operation		
Connectivity to the central heating system General technical approval for room sealed operation	Further important characteristics of the appliance	
General technical approval for room sealed operation	Suitability for installation to a shared flue ¹⁾	
	Connectivity to the central heating system	_
For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).	General technical approval for room sealed operation	
	1) For unsealed operation it is possible to install the appliances to	o a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2024 F - Crédit d'impôt à la transition énergétique

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing

Evaluation

D - 1.BlmSchV

According to the transitional rule §26 the appliance can be used until 31.12.2024

Emission evaluation legend



Compliant with the requirements of the 2nd stage of the 1.BImSchV (only for Germany)



Compliant with the requirements of the 1st stage of the 1.BImSchV (only for Germany)



Compliant with the requirements of the Austrian Agreement pursuant to Art. 15a B-VG from 2015 (applies only to Austria)



Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 7* of the Flamme Verte Label



Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 6* of the Flamme Verte Label



Compliant with the requirements for the "Crédit d'impôt" promotion in France, the fireplace complies with the classification 5* of the Flamme Verte Label



Compliant with the requirements of the 1 star stage in Italy.



Compliant with the requirements of the 2 star stage in Italy.



Compliant with the requirements of the 3 star stage in Italy.



Compliant with the requirements of the 4 star stage in Italy.



Compliant with the requirements of the 5 star stage in Italy.



Fulfils the requirements



Complies with requirements of the transition ruling (1.BImSchV)



Requirements are not fulfilled



No information/unknown



No measuring values are available for this fuel, operation with this fuel is not permitted

No symbol means that there are no requirements.

Here you will find further information