

Appliances properties: Supra S.A. - Saphir 1700D - Marke Worldkamin

Master data	
Date of entry	Feb 26, 2008
Manufacturer	Supra S.A.
Model	Saphir 1700D
Product code	Marke Worldkamin
Nominal heat output [kW]	10
Continuous burning appliance	_
Type test standard	DIN 18895
Year of testing	2005
Test laboratory	RWE Rheinbraun AG
Number of test laboratory	4.1
Number of test report	RB BF1-Hn 790

Flue	gas	values
1 100		

Wo	ood
Flue gas mass flow [g/s]	12
Flue gas mass flow [g/s]	300
Necessary flue draught [Pa]	12

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

General technical approval for room sealed operation

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm: Inset appliances (with closed firedoor) D - 1.BImSchV According to the transitional rule §26 the appliance can be used until 31.12.2024 A - Austrian regulation referred to Art 15a B-VG CH - Swiss clean air act F - Crédit d'impôt à la transition énergétique

Evaluation of emission data and efficiency Wood

Evaluation of emission data and efficiency Lignite briquett	tes
Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2024
A - Austrian regulation referred to Art 15a B-VG	_
CH - Swiss clean air act	!



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information