

Appliances properties: Supra S.A. - Tertio 69 D - Marke Eurokamin

Wood 7 388
Wood
RO-95 02 433
2
RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
1995
DIN 18895
_
8
Marke Eurokamin
Tertio 69 D
Supra S.A.
Feb 26, 2008

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Evaluation of emission data and efficiency Lignite briquettes	
Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	⋄
	Grandfathering
A - Austrian regulation referred to Art 15a B-VG	_
CH - Swiss clean air act	_



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information