

Appliances properties: Hark GmbH & Co. KG - Radiante 600

Master data

Date of entry Feb 27, 2015

Manufacturer Hark GmbH & Co. KG

Model Radiante 600

Nominal heat output [kW]

Continuous burning appliance

Type test standard DIN EN 13229

Year of testing 2014

Test laboratory Feuerstättenprüfstelle Kahl GmbH

Number of test laboratory

Number of test report FK 29 13 207

Flue gas values

| | Wood | Coal |
|-----------------------------|------|------|
| Flue gas mass flow [g/s] | 6.7 | 6.1 |
| Flue gas mass flow [g/s] | 307 | 355 |
| Necessary flue draught [Pa] | 12 | 12 |

28

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system



¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

| Norm : Inset appliances (with closed firedoor) | Evaluation |
|--|------------|
| D - 1.BlmSchV | Stufe 2 |
| A - Austrian regulation referred to Art 15a B-VG | _ |
| CH - Swiss clean air act | ✓ |
| F - Crédit d'impôt à la transition énergétique | ₹. |

Evaluation of emission data and efficiency Lignite briquettes

| Norm : Inset appliances (with closed firedoor) | Evaluation |
|--|------------|
| O - 1.BImSchV | Stufe 2 |
| A - Austrian regulation referred to Art 15a B-VG | ✓ |

CH - Swiss clean air act



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information