

Appliances properties: Supra S.A. - VERCORS - Marke Supra

Date of entry Feb 26, 2008 Manufacturer Supra S.A. Model VERCORS Product code Marke Supra Nominal heat output [kW] 9 Continuous burning appliance Type test standard DIN EN 13240 Year of testing 2004 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 Number of test report Elue gas values Wood Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s] 8 260 Necessary flue draught [Pa]			
Manufacturer Model VERCORS Product code Marke Supra Mominal heat output [kW] 9 Continuous burning appliance Type test standard DIN EN 13240 Year of testing 2004 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2004 Flue gas values Wood Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s]	Master data		
Model VERCORS Product code Marke Supra Nominal heat output [kW] 9 Continuous burning appliance	Date of entry	Feb 26, 2008	
Product code Marke Supra Nominal heat output [kW] 9 Continuous burning appliance Type test standard DIN EN 13240 Year of testing 2004 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 Number of test report 2004ES/102-EN13240 Flue gas walues Wood Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s] 260	Manufacturer	Supra S.A.	
Nominal heat output [kW] Continuous burning appliance Type test standard DIN EN 13240 Year of testing 2004 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 Number of test report DIN EN 13240 **Continuous burning appliance ### Continuous burning appliance ### C	Model	VERCORS	
Continuous burning appliance Type test standard Year of testing Test laboratory Number of test laboratory Number of test report Plue gas values Wood Flue gas mass flow [g/s] Flue gas mass flow [g/s] Flue gas mass flow [g/s] Plue gas mass flow [g/s]	Product code	Marke Supra	
Type test standard Year of testing 2004 Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2004ES/102-EN13240 Flue gas values Wood Flue gas mass flow [g/s] Flue gas mass flow [g/s] 2005 2006 2007 2007 2007 2007 2007 2007 2007	Nominal heat output [kW]	9	
Year of testing Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory Number of test report 2004ES/102-EN13240 Flue gas values Wood Flue gas mass flow [g/s] Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s]	Continuous burning appliance	_	
Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Number of test laboratory 2 Number of test report 2004ES/102-EN13240 Flue gas values Wood Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s] 260	Type test standard	DIN EN 13240	
Number of test laboratory 2 Number of test report 2004ES/102-EN13240 Flue gas values Wood Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s] 260	Year of testing	2004	
Number of test report 2004ES/102-EN13240 Flue gas values Wood Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s] 260	Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
Flue gas values Wood Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s] 260	Number of test laboratory	2	
Wood Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s] 260	Number of test report	2004ES/102-EN13240	
Wood Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s] 260			
Flue gas mass flow [g/s] 7 Flue gas mass flow [g/s] 260	Flue gas values		
Flue gas mass flow [g/s] 260			Wood
3.0	Flue gas mass flow [g/s]		7
Necessary flue draught [Pa] 12	Flue gas mass flow [g/s]		260
, , , , , , , , , , , , , , , , , , , ,	Necessary flue draught [Pa]		12

Further important characteristics of the appliance

Suitability for installation to a shared flue $^{1)}$



Connectivity to the central heating system



General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

DK - Danish regulation for air pollution from wood burners

F - Crédit d'impôt à la transition énergétique

Evaluation of emission data and efficiency Lignite briquettes			
Evaluation			
According to the transitional rule §26 the appliance can be used until 31.12.2024			
_			



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information