

Appliances properties: BRUNNER - Kamin-Kessel Tunnel 45/101 (18 kW)

Master data

Date of entryJun 18, 2012ManufacturerBRUNNER

Model Kamin-Kessel Tunnel 45/101 (18 kW)

Nominal heat output [kW]

Declared nominal space heating output [kW] 18

Continuous burning appliance

Type test standard DIN EN 13229

Year of testing 2011

Test laboratory TÜV SÜD Industrie Service GmbH

Number of test laboratory

Number of test report W-O 1323-00/11



Flue gas values

	Wood	
Flue gas mass flow [g/s]	16	
Flue gas mass flow [g/s]	145	
Necessary flue draught [Pa]	12	

18

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)

-

Connectivity to the central heating system



General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*}A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

orm : Inset appliances (with closed firedoor)	Evaluation
BlmSchV	Stufe 2
strian regulation referred to Art 15a B-VG	✓
Swiss clean air act	✓
- Crédit d'impôt à la transition énergétique	•

Evaluation of emission data and efficiency Lignite briquettes	
Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	1



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information