

Appliances properties: BRUNNER - HKD 2.2 SK Tunnel

Master data

Date of entryAug 27, 2014ManufacturerBRUNNER

Model HKD 2.2 SK Tunnel

Nominal heat output [kW] 12.3

Declared nominal space heating output [kW] 3

Nominal water heating output [kW] 8.4
Water operating pressure [bar] 3

Continuous burning appliance

Type test standard DIN EN 13229

Year of testing 2014

Test laboratory TÜV SÜD Industrie Service GmbH

Number of test laboratory

Number of test report W-O 1406-00/14



Flue gas values

	Wood
Flue gas mass flow [g/s]	8.4
Flue gas mass flow [g/s]	131
Necessary flue draught [Pa]	15

Further important characteristics of the appliance

Suitability for installation to a shared flue¹⁾



Connectivity to the central heating system



General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

orm : Inset appliance with flat-layer firing	Evaluation
1.BlmSchV	Stufe 2
ustrian regulation referred to Art 15a B-VG	✓
Swiss clean air act	✓
- Crédit d'impôt à la transition énergétique	✓

Evaluation of emission data and efficiency Lignite briquettes		
Norm : Inset appliance with flat-layer firing	Evaluation	
D - 1.BlmSchV	1	



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information