## Appliances properties: Spartherm Feuerungstechnik GmbH - Arte Uh 50 (Bauart A1 ; ab 2009)

Mar 6, 2012
Spartherm Feuerungstechnik GmbH
Arte Uh 50 (Bauart A1 ; ab 2009)
9
9
—
DIN EN 13229
2009
RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
2
RRF - 29 09 1933

Flue gas values

	Wood	
Flue gas mass flow [g/s]	8.6	
Flue gas mass flow [g/s]	310	
Necessary flue draught [Pa]	12	

Further important characteristics of the appliance	
Suitability for installation to a shared flue <sup>1)</sup>	•
Connectivity to the central heating system	-
General technical approval for room sealed operation	_

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

\* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

EU-Inset appliance according to EN13229	Evaluation
EU - Regulation (EU) 2015/1185 (Ecodesign)	
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	×
CH - Swiss clean air act	×
DK - Danish regulation for air pollution from wood burners	✓
F - Crédit d'impôt à la transition énergétique	7☆
I - Italian Decree No. 186	<b>***</b>

Evaluation of emission data and efficiency Ligr	nite briquettes
Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2024