

Appliances properties: Oranier Heiztechnik GmbH - 7610-10 Gala Prisma Eck Aqua - 7610 32

Master data

Date of entry Feb 25, 2011

ManufacturerOranier Heiztechnik GmbHModel7610-10 Gala Prisma Eck Aqua

Product code 7610 32
Nominal heat output [kW] 10.5

Type test standard DIN EN 13240

Year of testing 2010

Test laboratory RWE Rheinbraun AG

Number of test laboratory 4.1

Number of test report FSPS-Wa 1846-EN



Flue gas values

Continuous burning appliance


	Wood
Flue gas mass flow [g/s]	9
Flue gas mass flow [g/s]	170
Necessary flue draught [Pa]	13

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system



¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

orm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
1.BlmSchV	Stufe 2
Austrian regulation referred to Art 15a B-VG	✓

Evaluation of emission data and efficiency Lignite briquettes	
lorm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
- 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	/



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information