

Appliances properties: Rizzoli GmbH - RNVE50

Master data		
Date of entry	May 11, 2017	
Manufacturer	Rizzoli GmbH	
Model	RNVE50	
Nominal heat output [kW]	8	
Continuous burning appliance	_	
Type test standard	DIN EN 12815	
Year of testing	2015	
Test laboratory	ACTECO SRL	
Number of test laboratory	33	
Number of test report	1880-CPR-041-15	
Flue gas values		
		Wood
		10
Flue gas mass flow [g/s]		191.4
Flue gas mass flow [g/s]		
Flue gas mass flow [g/s]		191.4
Flue gas mass flow [g/s]		191.4
		191.4 9.6
Flue gas mass flow [g/s] Necessary flue draught [Pa]		191.4

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm : Cookers Evaluation Evaluation

D - 1.BlmSchV	Stufe 2 Grandfathering
- Austrian regulation referred to Art. 15a B-VG	2015
H - Swiss clean air act	✓
- Crédit d'impôt à la transition énergétique	✓.

Evaluation of emission data and efficiency Lignite briquettes

Norm : Cookers	Evaluation
D - 1.BImSchV	!

Evaluation of emission data and efficiency Pellets

Norm : Cookers	Evaluation
D - 1.BlmSchV	!



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information