

## Appliances properties: Spartherm Feuerungstechnik GmbH - Speedy 1Vh (Bauart A; ab 2006)

Late of entry Lanufacturer Spartherm Feuerungstechnik GmbH Speedy 1Vh (Bauart A; ab 2006) Spe			
Indufacturer  Indel Speedy 1Vh (Bauart A; ab 2006)  Iominal heat output [kW] 9  Iontinuous burning appliance  Iourninuous burninuous appliance  Iourninuous automatical appliance  Iourninuou	Master data		
Ideal Speedy 1Vh (Bauart A; ab 2006)  Ideal Ideal output [kW] 9  Ideal o	Date of entry	Dec 6, 1970	
tominal heat output [kW]  sominuous burning appliance  ype test standard  purply testing  gest laboratory  RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH  lumber of test laboratory  RRF - 29 06 1049  Flue gas values  Wood  lue gas mass flow [g/s]  ye gas mass flow [g/s]  seessary flue draught [Pa]  Further important characteristics of the appliance  unitability for installation to a shared flue 1)  connectivity to the central heating system	Manufacturer	Spartherm Feuerungstechnik GmbH	
protein transportance  Type test standard  DIN EN 13229  2006  Set laboratory  RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH  Lumber of test laboratory  2 RRF - 29 06 1049  Filue gas values  Wood  Lue gas mass flow [g/s]  Lu	Model	Speedy 1Vh (Bauart A; ab 2006)	
ype test standard  part of testing  gest laboratory  RRF Rhein-Ruhr-Feuerstattenprüfstelle GmbH  lumber of test laboratory  RRF - 29 06 1049  Flue gas values  Wood  lue gas mass flow [g/s]  lue ga	Nominal heat output [kW]	9	
ear of testing est laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH lumber of test laboratory RRF - 29 06 1049  Flue gas values  Wood  lue gas mass flow [g/s] lue gas mass flow [g/s] secessary flue draught [Pa]  Further important characteristics of the appliance  uitability for installation to a shared flue <sup>1)</sup> connectivity to the central heating system	Continuous burning appliance	_	
RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH Jumber of test laboratory Jumber of test report  RRF - 29 06 1049  Filue gas values  Wood Jue gas mass flow [g/s]  J	Type test standard	DIN EN 13229	
tumber of test laboratory tumber of test report  RRF - 29 06 1049  File gas values  Wood  Rue gas mass flow [g/s] Lue gas mass flow [g/s] Secessary flue draught [Pa]  Further important characteristics of the appliance	Year of testing	2006	
Flue gas values  Wood  lue gas mass flow [g/s] 9.2  lue gas mass flow [g/s] 336  lecessary flue draught [Pa] 12  Further important characteristics of the appliance  Further important characteristics of the appliance  Further important characteristics of the appliance  Fornnectivity to the central heating system	Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
Flue gas values  Wood  Jue gas mass flow [g/s] 9.2  Jue gas mass flow [g/s] 336  Jue gas mass flow [g/s] 12  Further important characteristics of the appliance  Further important characteristics of the appliance  Further important characteristics of the appliance  Fornectivity to the central heating system	Number of test laboratory	2	
Wood  Tue gas mass flow [g/s]  Plue gas mass flow [g/s]  Secessary flue draught [Pa]  Further important characteristics of the appliance  Further installation to a shared flue 1)  Connectivity to the central heating system	Number of test report	RRF - 29 06 1049	
lue gas mass flow [g/s] 336 lecessary flue draught [Pa] 12  Further important characteristics of the appliance  suitability for installation to a shared flue 1)  connectivity to the central heating system			Wood
Further important characteristics of the appliance  suitability for installation to a shared flue 1)  connectivity to the central heating system	Flue gas mass flow [g/s]		9.2
Further important characteristics of the appliance  suitability for installation to a shared flue <sup>1)</sup> connectivity to the central heating system	Flue gas mass flow [g/s]		336
cuitability for installation to a shared flue <sup>1)</sup> connectivity to the central heating system	Necessary flue draught [Pa]		12
cuitability for installation to a shared flue <sup>1)</sup> connectivity to the central heating system			
Connectivity to the central heating system	Further important characteristics of the appliance		
	Suitability for installation to a shared flue <sup>1)</sup>		_
eneral technical approval for room sealed operation	Connectivity to the central heating system		_
	General technical approval for room sealed operation		_

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>\*</sup> A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Evaluation of emission data and efficiency Wood

EU-Inset appliance according to EN13229	Evaluation
EU - Regulation (EU) 2015/1185 (Ecodesign)	✓
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	<b>*</b>
CH - Swiss clean air act	✓
DK - Danish regulation for air pollution from wood burners	✓
F - Crédit d'impôt à la transition énergétique	7☆
I - Italian Decree No. 186	資金資

## Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor) Evaluation

D - 1.BImSchV

According to the transitional rule §26 the appliance can be used until 31.12.2024



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information