Appliances properties: Krog Iversen & Co. A/S - Scan 63

Master data Jun 4, 2011 Date of entry Manufacturer Krog Iversen & Co. A/S Model Scan 63 Nominal heat output [kW] 6 **Continuous burning appliance** Type test standard **DIN EN 13240** Year of testing 2009 **Test laboratory** Danish Technological Institute Number of test laboratory 15 Number of test report 300-ELAB-1330-EN

Flue gas values

	Wood	
Flue gas mass flow [g/s]	7.2	
Flue gas mass flow [g/s]	289	
Necessary flue draught [Pa]	12	

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	-
General technical approval for room sealed operation	-

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
) - 1.BImSchV	Stufe 2
- Austrian regulation referred to Art 15a B-VG	-
H - Swiss clean air act	×
0K - Danish regulation for air pollution from wood burners	×
- Crédit d'impôt à la transition énergétique	

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing

Evaluation

D - 1.BlmSchV

According to the transitional rule §26 the appliance can be used until 31.12.2024

L