

Appliances properties: Supra S.A. - INSERT 654 - Marke Supra

Master data	
Date of entry	Feb 26, 2008
Manufacturer	Supra S.A.
Model	INSERT 654
Product code	Marke Supra
Nominal heat output [kW]	10
Continuous burning appliance	_
Type test standard	DIN EN 13229
Year of testing	2006
Test laboratory	SGS Nederland B.V.
Number of test laboratory	11
Number of test report	SGS-5970-43-12-06
Flue gas values	
	Wood

	Wood
Flue gas mass flow [g/s]	7
Flue gas mass flow [g/s]	388
Necessary flue draught [Pa]	14

Further important characteristics of the appliance

Suitability for installation to a shared flue $^{1)}$



Connectivity to the central heating system

_

General technical approval for room sealed operation

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Evaluation of emission data and efficiency Lignite briquettes		
Norm : Inset appliances (with closed firedoor)	Evaluation	
D - 1.BlmSchV	⋄	
	Grandfathering	
A - Austrian regulation referred to Art 15a B-VG	_	
CH - Swiss clean air act	_	



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information