

Appliances properties: Palazzetti Lelio S. p. A. - ECOMONOBLOCCO 66 O2RING

Master data			
Date of entry	Mar 8, 2013		
Manufacturer	Palazzetti Lelio S. p. A.		
Model	ECOMONOBLOCCO 66 O2RING		
Nominal heat output [kW]			
Continuous burning appliance	_		
Type test standard	DIN EN 13229		
Year of testing	2012		
Test laboratory	TÜV RHEINLAND INDUSTRIE SERVICE GMBH - TÜV Rheinland Group		
Number of test laboratory	5		
Number of test report	K 706 2012 T1		
Flue gas wass flow [g/s]		Wood 14.7	
Flue gas mass flow [g/s]		256.9	
Necessary flue draught [Pa]		11	
Further important characteristics of the a	appliance		
Suitability for installation to a shared flue ¹⁾			
Connectivity to the central heating system			
General technical approval for room sealed operation			

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

orm : Inset appliance with flat-layer firing	Evaluation
1.BImSchV	Stufe 2
ustrian regulation referred to Art 15a B-VG	✓
Swiss clean air act	✓
Crédit d'impôt à la transition énergétique	•

Evaluation of emission data and efficiency Lignite briquettes				
Norm : Inset appliance with flat-layer firing	Evaluation			
D - 1.BlmSchV	1			



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information