Appliances properties: Olsberg GmbH - Olsberg - Pacaya Compact

Master data	
Date of entry	Jan 5, 2016
Manufacturer	Olsberg GmbH - Olsberg
Model	Pacaya Compact
Nominal heat output [kW]	6.8
Continuous burning appliance	—
Type test standard	DIN EN 13240
Year of testing	2015
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test laboratory	2
Number of test report	RRF - 40 15 4047

Flue gas values

	Wood
Flue gas mass flow [g/s]	5.8
Flue gas mass flow [g/s]	336
Necessary flue draught [Pa]	12

 Further important characteristics of the appliance

 Suitability for installation to a shared flue¹⁾

 Connectivity to the central heating system

 General technical approval for room sealed operation

 Number of approval for room sealed operation

 Z-43.12-398

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
) - 1.BImSchV	Stufe 2
- Austrian regulation referred to Art 15a B-VG	2015
:H - Swiss clean air act	•
K - Danish regulation for air pollution from wood burners	×
- Crédit d'impôt à la transition énergétique	

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation	
D - 1.BImSchV		