

## Appliances properties: Palazzetti Lelio S. p. A. - ECOMONOBLOCCO 86 O2RING

Master data Date of entry Mar 8, 2013 Manufacturer Palazzetti Lelio S. p. A. Model ECOMONOBLOCCO 86 O2RING Nominal heat output [kW] 26.8 Continuous burning appliance Type test standard **DIN EN 13229** 2012 Year of testing **Test laboratory** TÜV RHEINLAND INDUSTRIE SERVICE GMBH - TÜV Rheinland Group Number of test laboratory Number of test report K 708 2012 T1 Flue gas values Wood Flue gas mass flow [g/s] 20.3 Flue gas mass flow [g/s] 320 Necessary flue draught [Pa] 11 Further important characteristics of the appliance Suitability for installation to a shared flue<sup>1)</sup> Connectivity to the central heating system General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

<sup>\*</sup>A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

orm : Inset appliance with flat-layer firing	Evaluation
1.BlmSchV	Stufe 2
ustrian regulation referred to Art 15a B-VG	✓
Swiss clean air act	✓
Crédit d'impôt à la transition énergétique	<b>✓</b>

Evaluation of emission data and efficiency Lignite briquettes		
Norm : Inset appliance with flat-layer firing	Evaluation	
D - 1.BlmSchV	1	



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information