Appliances properties: Olsberg GmbH - Olsberg - Pago Compact RLU - 23/369

Master data		
Date of entry Manufacturer	Jan 9, 2008 Olsberg GmbH - Olsberg	
Model Product code	Pago Compact RLU 23/369	THE OWNER OF
Nominal heat output [kW]	8	
Continuous burning appliance	—	
Type test standard	DIN 18891	
Year of testing	2004	
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH	
Number of test laboratory	2	
Number of test report	RO-9104687	

Flue gas values

Wood	
8	
310	
11	

Further important characteristics of the appliance	
(
Switchillity for installation to a shared flue 1	_
Suitability for installation to a shared flue ¹⁾	_
Connectivity to the central heating system	_
· · · · · · · · · · · · · · · · · · ·	
General technical approval for room sealed operation	• • • • • • • • • • • • • • • • • • •
Number of approval for room sealed operation	Z-43.12-179
	2 40.12 170

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Grandfathering
A - Austrian regulation referred to Art 15a B-VG	×
CH - Swiss clean air act	×
DK - Danish regulation for air pollution from wood burners	_
F - Crédit d'impôt à la transition énergétique	×

##