

## Appliances properties: Dovre N.V. - Vintage 50

Master data

Date of entry

Manufacturer

Dovre N.V.

Model

Vintage 50

Nominal heat output [kW]

Declared nominal space heating output [kW]

Continuous burning appliance

Type test standard

Year of testing

Dovre N.V.

Vintage 50

9

Dovre N.V.

Vintage 50

Policy

Policy

Policy

DIN EN 13240

2010

Test laboratory LABORATORY K.V.B.G. - A.R.G.B.

Number of test laboratory17Number of test reportH0075



Flue gas values

	Wood
Flue gas mass flow [g/s]	6.4
Flue gas mass flow [g/s]	328
Necessary flue draught [Pa]	12

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

\* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

## Evaluation of emission data and efficiency Wood Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing Evaluation D - 1.BImSchV Stufe 2 CH - Swiss clean air act ✓ F - Crédit d'impôt à la transition énergétique ✓

Evaluation of emission data and emiciency Lightle briqueties	
Norm DIN EN 42340 (Intermittant huming). Deembester with flat lever firing	Evaluation
Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation

D - 1.BlmSchV



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information