

## Appliances properties: Dovre N.V. - Vintage 35

Master data

Date of entry Dec 27, 2011 Dovre N.V. Manufacturer Model Vintage 35 Nominal heat output [kW] Declared nominal space heating output [kW] Continuous burning appliance **DIN EN 13240** Type test standard Year of testing 2011 LABORATORY K.V.B.G. - A.R.G.B. **Test laboratory** Number of test laboratory 17



Flue gas values

Number of test report

|                             | Wood |
|-----------------------------|------|
| Flue gas mass flow [g/s]    | 4.9  |
| Flue gas mass flow [g/s]    | 298  |
| Necessary flue draught [Pa] | 12   |

H0083

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

\* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

## Evaluation of emission data and efficiency Wood Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing Evaluation D - 1.BImSchV Stufe 2 CH - Swiss clean air act ✓ F - Crédit d'impôt à la transition énergétique ✓

| Evaluation of emission data and emiciency Lightle briqueties                |            |
|---|------------|
| Norm DIN EN 42340 (Intermittant huming). Deembester with flat lever firing  | Evaluation |
| Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing | Evaluation |

D - 1.BlmSchV



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information