

Appliances properties: Fireplace Kft - K 1381 Belfegor

Master data

Date of entry Jun 20, 2005

Manufacturer Fireplace Kft

Model K 1381 Belfegor

Nominal heat output [kW]

Continuous burning appliance

Type test standard DIN EN 13240

Year of testing 2005

Test laboratory TNO Science and Industry

Number of test laboratory

Number of test report 2005PMC/063

Flue gas values

	Wood	Coal
Flue gas mass flow [g/s]	7.1	7.7
Flue gas mass flow [g/s]	249	246
Necessary flue draught [Pa]	12	12

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system



General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing Evaluation D - 1.BImSchV Stufe 2 F - Crédit d'impôt à la transition énergétique 7★

Evaluation of emission data and efficiency Lignite briquettes	
Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Grandfathering



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information