

## Appliances properties: skantherm GmbH & Co. KG - samsø I (mehrfachbelegbar)

| Master data   |                               |          |
|---|-------------------------------|----------|
| Date of entry   | Mar 6, 2012                   |          |
| Manufacturer  | skantherm GmbH & Co. KG       |          |
| Model   | samsø I (mehrfachbelegbar)    |          |
| Nominal heat output [kW]                                    | 6                             |          |
| Continuous burning appliance                                | _                             |          |
| Type test standard  | DIN 18891                     |          |
| Year of testing   | 1994                          |          |
| Test laboratory   | Deutsche Kohle Marketing GmbH |          |
| Number of test laboratory                                   | 22                            |          |
| Number of test report                                       | 91 92 38                      |          |
| Flue are value  |                               |          |
| Flue gas values   |                               |          |
|   |                               | Wood     |
| Flue gas mass flow [g/s]                                    |                               | 7        |
| Flue gas mass flow [g/s]                                    |                               | 260      |
| Necessary flue draught [Pa]                                 |                               | 12       |
|   |                               |          |
| Further important characteristics of the appliance          |                               |          |
| Suitability for installation to a shared flue <sup>1)</sup> |                               | <b>*</b> |
| Connectivity to the central heating system                  |                               | _        |
| General technical approval for room sealed operation        |                               | _        |

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>\*</sup> A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Evaluation of emission data and efficiency Wood

| Norm DIN EN 13240: Roomheater for wood logs                | Evaluation  |
|--|---|
| EU - Regulation (EU) 2015/1185 (Ecodesign)                 | !   |
| D - 1.BlmSchV  | According to the transitional rule §26 the appliance can be used until 31.12.2020 |
| A - Austrian regulation referred to Art 15a B-VG           |   |
| CH - Swiss clean air act                                   |   |
| DK - Danish regulation for air pollution from wood burners |   |
| F - Crédit d'impôt à la transition énergétique             | ļ.  |
| I - Italian Decree No. 186                                 | !   |

## Evaluation of emission data and efficiency Lignite briquettes

| Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing | Evaluation  |
|---|---|
| D - 1.BlmSchV   | According to the transitional rule §26 the appliance can be used until 31.12.2020 |



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information