Appliances properties: Spartherm Feuerungstechnik GmbH - Mini 2L (Bauart A1; ab 2008)

Master data	
Date of entry	Jul 19, 2012
Manufacturer	Spartherm Feuerungstechnik GmbH
Model	Mini 2L (Bauart A1; ab 2008)
Nominal heat output [kW]	7
Continuous burning appliance	—
Type test standard	DIN EN 13229
Year of testing	2008
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test laboratory	2
Number of test report	RRF-29 07 1206

Flue gas values

Wood	
6	
330	
12	

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	_
General technical approval for room sealed operation	-

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

EU-Inset appliance according to EN13229	Evaluation
EU - Regulation (EU) 2015/1185 (Ecodesign)	×
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	×
CH - Swiss clean air act	✓
DK - Danish regulation for air pollution from wood burners	<
F - Crédit d'impôt à la transition énergétique	7☆
I - Italian Decree No. 186	大

Evaluation of emission data and efficiency Lignite briquettes		
Norm : Inset appliances (with closed firedoor)	Evaluation	
D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2024	