

Appliances properties: Brula GmbH - BRULA Feuerraum Typ D plus 90° L

, 2023 GmbH A Feuerraum Typ D plus 90° L 10	
GmbH A Feuerraum Typ D plus 90° L 00	
GmbH A Feuerraum Typ D plus 90° L 00	
A Feuerraum Typ D plus 90° L	
0	
N 15250	
astechnisches Institut gGmbH Freiberg	
2/0815	
Wood	
24.56	
198	
13	
	*

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Wood

Norm : Masonry heater	Evaluation
D - 1.BlmSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	✓
CH - Swiss clean air act	✓
F - Crédit d'impôt à la transition énergétique	*

Evaluation of emission data and efficiency Lignite briquettes

Norm : Masonry heater	Evaluation
D - 1.BlmSchV	ļ.



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information