

Appliances properties: Hase Kaminofenbau GmbH - Loggia

Master data	
Date of entry	Nov 15, 2011
Manufacturer	Hase Kaminofenbau GmbH
Model	Loggia
Nominal heat output [kW]	5
Continuous burning appliance	_
Type test standard	DIN 18891
Year of testing	1997
Test laboratory	RWE Rheinbraun AG
Number of test laboratory	4.1
Number of test report	RB BF1-Hn 34/97
Flue gas values	
	Wood
Flue gas mass flow [g/s]	6
Flue gas mass flow [g/s]	330
Necessary flue draught [Pa]	11
Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	_
Connectivity to the central heating system	_

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing D - 1.BImSchV F - Crédit d'impôt à la transition énergétique Evaluation Evaluation F - Crédit d'impôt à la transition énergétique

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing

Evaluation

D - 1.BImSchV





No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information