Appliances properties: Spartherm Feuerungstechnik GmbH - Speedy E-FDh (Bauart A; ab 2007)

Master data	
Date of entry	Mar 6, 2012
Manufacturer	Spartherm Feuerungstechnik GmbH
Model	Speedy E-FDh (Bauart A; ab 2007)
Nominal heat output [kW]	8
Continuous burning appliance	—
Type test standard	DIN EN 13229
Year of testing	2007
Test laboratory	RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH
Number of test laboratory	2
Number of test report	RRF - 29 07 1098

Flue gas values

	Wood	
Flue gas mass flow [g/s]	7	
Flue gas mass flow [g/s]	320	
Necessary flue draught [Pa]	12	

Further important characteristics of the appliance		
Suitability for installation to a shared flue ¹⁾	-	
Connectivity to the central heating system	-	
General technical approval for room sealed operation	-	

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission	data and efficiency Wood
------------------------	--------------------------

EU-Inset appliance according to EN13229	Evaluation
EU - Regulation (EU) 2015/1185 (Ecodesign)	-
D - 1.BImSchV	Stufe 1 Grandfathering
A - Austrian regulation referred to Art 15a B-VG	×
CH - Swiss clean air act	×
DK - Danish regulation for air pollution from wood burners	-
F - Crédit d'impôt à la transition énergétique	6 ☆
I - Italian Decree No. 186	र्भ प्रेन्स

Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BImSchV	According to the transitional rule §26 the appliance can be used until 31.12.2024