

Continuous burning appliance

## Appliances properties: Barbas BV - Unilux 55

Master data

Date of entryJun 22, 2010ManufacturerBarbas BVModelUnilux 55Nominal heat output [kW]11

Type test standard DIN EN 13229

Year of testing 2010

Test laboratory SGS Nederland B.V.

Number of test laboratory

Number of test report EZ/09/2694-12



Flue gas values

	Wood
Flue gas mass flow [g/s]	9
Flue gas mass flow [g/s]	288
Necessary flue draught [Pa]	12

11

Further important characteristics of the appliance

Suitability for installation to a shared flue<sup>1)</sup>

Connectivity to the central heating system

## General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

<sup>\*</sup> A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

orm : Inset appliances (with closed firedoor)	Evaluation
1.BImSchV	Stufe 2
ustrian regulation referred to Art 15a B-VG	_
Swiss clean air act	✓
Crédit d'impôt à la transition énergétique	<b>✓</b>

Evaluation of emission data and efficiency Lignite briquettes	
Norm : Inset appliances (with closed firedoor)	Evaluation
D - 1.BlmSchV	I



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information