Appliances properties: Krog Iversen & Co. A/S - Scan 25

Master data	
Date of entry	Jun 4, 2011
Manufacturer	Krog Iversen & Co. A/S
Model	Scan 25
Nominal heat output [kW]	5
Continuous burning appliance	-
Type test standard	DIN EN 13240
Year of testing	2007
Test laboratory	RWE Rheinbraun AG
Number of test laboratory	4.1
Number of test report	FSPS-Wa 1266-1-EN

 Flue gas values
 Wood

 Flue gas mass flow [g/s]
 5

 Flue gas mass flow [g/s]
 310

 Necessary flue draught [Pa]
 11

Further important characteristics of the appliance	
Suitability for installation to a shared flue ¹⁾	
Connectivity to the central heating system	_
General technical approval for room sealed operation	-

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

* A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Stufe 2
A - Austrian regulation referred to Art 15a B-VG	×
CH - Swiss clean air act	•
0K - Danish regulation for air pollution from wood burners	×
- Crédit d'impôt à la transition énergétique	

Evaluation of emission data and efficiency Lignite briquettes

Norm DIN EN 13240 (Intermittent burning): Roomheater with flat-layer firing	Evaluation
D - 1.BImSchV	Stufe 1 Grandfathering
A - Austrian regulation referred to Art 15a B-VG	×
CH - Swiss clean air act	×