

Appliances properties: Palazzetti Lelio S. p. A. - ECOMONOBLOCCO S 25-9 BIFACCIALE

Master data		
Date of entry	Mar 8, 2013	
Manufacturer	Palazzetti Lelio S. p. A.	
Model	ECOMONOBLOCCO S 25-9 BIFACCIALE	
Nominal heat output [kW]	21.8	
Continuous burning appliance	_	
Type test standard	DIN EN 13229	
Year of testing	2010	
Test laboratory	KIWA GASTEC ITALIA S.P.A.	
Number of test laboratory	6	
Number of test report	101100929	
Flue gas values		Wood
Flue gas mass flow [g/s]		23.7
Flue gas mass flow [g/s] Necessary flue draught [Pa]		228.1 12
Necessary nue draught [r a]		12
Further important characteristics of the appliance		
Suitability for installation to a shared flue ¹⁾		-
Connectivity to the central heating system		_
General technical approval for room sealed operation		_
1) For unsealed operation it is possible to install the appliances to a s	shared flue system (please see installation manual).	

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*} A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Evaluation of emission data and efficiency Lignite briquettes

Evaluation of emission data and efficiency Wood

Norm : Inset appliance with flat-layer firing	Evaluation
D - 1.BImSchV	I



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information