

## Appliances properties: Supra S.A. - Tertio 76 VL1D - Marke Supra

s, 2008 S.A. 76 VL1D Supra
76 VL1D
Supra
8895
hein-Ruhr-Feuerstättenprüfstelle GmbH
98 144
Wood
8
420
14
2

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)

Connectivity to the central heating system

General technical approval for room sealed operation

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements\* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

<sup>1)</sup> For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

<sup>\*</sup> A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

## Norm: Inset appliances (with closed firedoor) D - 1.BImSchV F - Crédit d'impôt à la transition énergétique Evaluation Evaluation Grandfathering

## Evaluation of emission data and efficiency Lignite briquettes

Norm : Inset appliances (with closed firedoor)

Evaluation

D - 1.BImSchV





No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information