

Master data

Product code

Appliances properties: Supra S.A. - Tertio 67 VL 2D - Marke Supra

Date of entryFeb 26, 2008ManufacturerSupra S.A.ModelTertio 67 VL 2D

Nominal heat output [kW]

Continuous burning appliance

Type test standard DIN 18895
Year of testing 1995

Test laboratory RRF Rhein-Ruhr-Feuerstättenprüfstelle GmbH

Number of test laboratory 2

Number of test report RO-95 98 145

Flue gas values

	Wood
Flue gas mass flow [g/s]	7
Flue gas mass flow [g/s]	388
Necessary flue draught [Pa]	14

Marke Supra

Further important characteristics of the appliance

Suitability for installation to a shared flue 1)



Connectivity to the central heating system

General technical approval for room sealed operation

¹⁾ For unsealed operation it is possible to install the appliances to a shared flue system (please see installation manual).

On behalf of the manufacturer, the HKI Industrieverband e.V. hereby confirms compliance with the respective requirements* in accordance with 1.BImSchV. The type test report of the fireplace has been submitted to the HKI Industrieverband e.V.

^{*}A green check mark with a "1" indicates that the requirements of the 1st BImSchV are fulfilled, a green check mark with a "2" indicates that the 2nd level of the 1st BImSchV is fulfilled. A yellow check mark shows that the transitional regulation of the 1st BImSchV is fulfilled and a red line means that the 1st BImSchV is not fulfilled.

Norm: Inset appliances (with closed firedoor) D - 1.BImSchV A - Austrian regulation referred to Art 15a B-VG CH - Swiss clean air act F - Crédit d'impôt à la transition énergétique Evaluation Evaluation

According to the transitional rule §26 the appliance can be used until 31.12.2024

D - 1.BImSchV

CH - Swiss clean air act

A - Austrian regulation referred to Art 15a B-VG



No symbol means that there are no requirements.

No measuring values are available for this fuel, operation with this fuel is not permitted

Here you will find further information